

### Action code: WHEN CONVENIENT

# **PMI** sensor calibration requirements

SL2019-672/CHSO June 2019

### Concerns

Owners and operators of MAN B&W two-stroke marine diesel engines. Type: MC/MC-C and ME/ME-C

## **Summary**

High-quality pressure measurements can be ensured by calibrating the sensors in accordance with the proper requirements and recommendations.

••••••

Dear Sir or Madam

This Service Letter specifies the IMO requirements and manufacturer recommendations regarding calibration of the PMI pressure sensors, the calibration sensors, and the calibration box for engines in service. High quality measurements will be ensured by following the requirements and recommendations listed in this letter.

Yours faithfully

**Michael Petersen** 

Vice President

PrimeServ Two-stroke

Stig Holm Senior Manager

**Technical Service** 

Teglholmsgade 41 2450 Copenhagen SV Denmark

Phone: +45 33 85 11 00 +45 33 85 10 30 info-cph@man-es.com www.man-es.com

Teglholmsgade 41 2450 Copenhagen SV Denmark

Phone: +45 33 85 11 00 Fax: +45 33 85 10 49 PrimeServ-cph@man-es.com Production

Teglholmsgade 35 2450 Copenhagen SV Denmark

Phone: +45 33 85 11 00 Fax: +45 33 85 10 17 manufacturing-dk@man-es.com Forwarding & Receiving

Teglholmsgade 35 2450 Copenhagen SV Denmark

Phone: +45 33 85 11 00 Fax: +45 33 85 10 16 shipping-cph@man-es.com **MAN Energy Solutions** 

Branch of MAN Energy Solutions SE. Germany CVR No.: 31611792 Head office: Teglholmsgade 41 2450 Copenhagen SV, Denmark German Reg.No.: HRB 22056 Amtsgericht Augsburg



# **Calibration interval**

IMO requirements: IMO Marpol Annex VI,  ${\rm NO_x}$  Technical code, App. 4, §1.3.2. Calibration.

	Sensor type	Calibration interval	Calibration certificate	Identification (for reference only)
IMO requirements	Fixed pressure sensor	12 months* (verification every 6 months is recommended)	No	
	PMI offline pressure sensor	12 months	Yes	
Manufacturer's recommendations	Calibration sensor	5 years	Yes	
	Calibration box	5 years	Yes	First Confidence State  Age of Equation  To the State of Equation  To the State of Equation  The State of Equation

<sup>\*</sup> Traceable calibration on the engine by using the PMI calibration sensor. New certificate not required.



### Fixed pressure sensor

The fixed sensors are used for engine performance measurements, PMI Auto-tuning, which is initially calibrated when the system is commissioned.

In service, the fixed sensors are calibrated on the engine using the calibration sensor and the calibration box. Re-calibration must be performed at least once every 12 months. However, it is recommended to check the fixed sensor calibration more frequently, e.g. every 6 months.

Note: Do not blow through before connecting the calibration sensor. The high temperatures seen during blow through are known to damage the fixed sensors.

Our Service Letter SL2016-621 Lifetime of Fixed Cylinder Pressure Sensors provides more information about precautionary measures and maintenance of the sensors.

#### PMI offline pressure sensor

PMI offline sensors are used for engine performance measurements. Re-calibration must be performed at least once every 12 months at an approved calibration center and according to the manufacturer's specifications.

The sensor should be calibrated together with the PMI calibration box and the connection cable.

### Calibration sensor and calibration box

The calibration sensor is a certified, traceable calibrated sensor which is accompanied by a calibration certificate. The calibration sensor and the calibration box must be recalibrated minimum every 5 years at an approved calibration center and according to the manufacturer's specifications.

The calibration sensor should be calibrated together with the calibration box and the connection cable.

The calibration sensor is dedicated to the calibration of the fixed pressure sensors only. Using the sensor for any other purpose, such as frequently performing a manual engine performance measurement, will cause the calibration certificate to expire after 12 months in service.

For calibration or repair of the sensor and calibration box, or for general questions regarding this Service Letter, please contact MAN PrimeServ at:

CalibrationService-CPH@man-es.com